## TECHNICAL DRAWINGS

#### Ovens are equipped with 6' electrical (FOR GAS OVENS ONLY) 3/8" NPT gas connection cord with 20 amps plug (120 volts). 96 3/8"(2448mm) **Ventilation:** 4 1/4"(108mm) Proper ventilation is required. 12 3/8"(314mm) Must be installed under ventilation hood. 53"(1346mm) Conveyor belt direction 4 1/4"(108mm) 33 1/4"(845mm) Right -50"(1270mm) 1 5/8"(41mm) Left 68"(1727mm) 61 5/8"(1553mm) 25"(635mm) 45 1/2"(1156mm) 11"(279mm) J 20 1/2"(521mm) 18"(457mm) 24"(610mm)

## **SPECIFICATIONS**

### **Electric**

MODEL	C3260E		
ELECTRIC ELEMENTS / KW	9 X 4.5 kw) = 40.5 kw)		
EXTERIOR DIMENSIONS	96"L X 50"D   244 cm x127 cm		
LENGTH OF BELT	96"L X 32"D   244 cm x81 cm		
VOLTAGES	208V/3PH 114 AMPS 220/1PH 192 AMPS 2401PH 209 AMPS		
SHIP WT	1090 lbs   495 kg		

Available in 50 or 60 cycles. Amperage could vary if input volts are not the same as indicated.







Gas connection: Equipped with 3/4" NPT gas connection at rear.

**Electrical:** 

C3260E - C3260G

APPROXIMATE PRODUCTION PER HOUR / PER SECTION / BAKE TIME IN MINUTES (3248)									
PAN DIAMETER	5 min	6 min	6.45 min	7 min	7.5 min	8 min	9 min		
6" (15 cm)	632	531	495	455	423	397	353		
8" (20 cm)	357	298	277	255	237	223	198		
10" (25 cm)	227	190	176	161	151	141	125		
12"(30 cm)	157	131	121	111	104	98	86		
14" (35 cm)	115	95	89	81	76	71	64		
16" (40 cm)	88	73	67	61	58	53	48		

Cooking Chamber on Electric and Gas 60" (152.4 cm) long X 32" (81 cm) deep

#### Gas

MODEL	C3260G
B.T.U.	160,000
EXTERIOR DIMENSIONS	96"L X 50"D   244 cm x 127 cm
LENGTH OF BELT	96"L X 32"D   244 cm x81 cm
VOLTAGES	110/1PH 14 AMPS
SHIP WT	1090 lbs   495 kg

Propane or Natural Gas also available in 50 or 60 cycles Warranty: 12 months parts & labor.

#### **Gas requirements**

**Gas Connection:** 3/4" NPT on the right hand rear of the appliance.

Gas pressure: 3.5" W.C. - Natural Gas | 10" W.C. - Propane

**Combustible Clearances:** For use in non-combustible locations | Non-combustible Clearances: 3" inches sides, 3" inches rear. Specify type of gas and altitude. If over 2,000 feet when ordering, a restraining kit is required for ovens installed with a caster kit. Check your local code.

#### **SIERRA RANGE** is a registered trademark of MVP Group.

Due to continuing product development, to ensure best possible performance, the specifications are subject to change without prior notice.

# SOMERSET

Tel: 978.667.3355 800.772.4404 Fax: 978.671.9466

www.smrset.com

Email: somerset@smrset.com



# **CDR-100**

# **DOUGH SHEETER**

#### **IDEAL FOR:**

- Cinnamon Rolls
- Yeast Raised Donuts
- Danishes
- Pastry Production
- Dough Lamination
- Pie Crusts
- Pizza 10" Max (25cm)
- Pasta
- Fondant

#### **HIGHLIGHTS:**

- Sheets dough up to 10" (25cm wide)
- Ships standard with synthetic, non-stick rollers
- Sheets 500-600pcs. per hour
- Ergonomic design makes it easy and simple to operate
- All stainless steel construction offers safety, sanitation, speed, simplicity, durability, and low cost



SOMERSET INDUSTRIES, INC • 1 ESQUIRE ROAD • NORTH BILLERICA, MA 01862 • U.S.A.