TECHNICAL SCHEME

SPIKA NG 360

SIDE VIEW



FRONTAL VIEW



REAR VIEW



*** All dimensions in inches (and mm)**

OPERATING CONDITIONS

PRODUCTION (LBS) 60Hz

- ±10% V
- 41ºF/109ºF
- 41ºF/95ºF
- 14,5 psi (1 bar) /87 psi(6 bar)
- 144/288 Ice cubes/cycle

V	Hz	ph
115	60	1N

FULL DICE — SPIKA NG 360 AIR COOLED (24 H, lbs)

ºF / ºC	50º / 10º	60º / 15º	70º / 21º	86º / 30º
50º / 10º	335	344	348	337
68º / 21º	353	346	337	331
90º / 32º	302	298	282	271
109º / 43º	247	243	227	214

FULL DICE — SPIKA NG 360 WATER COOLED (24 H, lbs)

ºF / ºC	50º / 10º	60º / 15º	70º / 21º	86º / 30º
50º / 10º	-	-	-	-
68º / 21º	-	-	-	-
90º / 32º	-	-	-	-
109º / 43º	-	-	-	-

MODELS	+cº / -cº	ASHRAE CONDITIONS (BTu/h)	(W)	(W) 109ºF	(AWG/mm²)	(n.)	FUSE	100lbs 90ºF / 70ºF (Kwh/100 lbs)	gal / 100lbs	(l/h)	HEAT REJECTED (BTu/h)	(W)	(lbs)	(lbs)
SPIKA NG 360 A		6,791	1,989	750	16/1,5	3	16	5.8	23	10.2	5,353	1,568	163	187,5
SPIKA NG 360 W		-	-	-	-	-	-	-	-	-	-	-	-	-

ITV Ice Makers, Inc.
9550 Satellite Blvd, Suite 100
Orlando, FL 32837
Phone: 1 407 826 1860 | Fax: 1 407 826 1861
Toll Free: 1 888 488 1423
sales@itvice.com | www.itvice.com

TECHNICAL ASSISTANCE
SERVICE
service@itvice.com
Skype: service@itvice.com
PHONE: +1 888 488 1423
FROM 8AM TO 5PM EST

3 YEARS WARRANTY PARTS & LABOR
2 ADDITIONAL YEARS ON COMPRESSOR & EVAPORATOR
Read our warranty policy to know more about limitations and exclusions

VERTICAL SYSTEM

0000_itvice/en_11/B/21

ITV ICE makers



3 YEARS WARRANTY PARTS & LABOR

SPIKA NG 285

115 V / 60 Hz

SELF-CONTAINED ICE CUBE MACHINE

FEATURES

- PRODUCES FULL DICE ICE CUBES OR HALF DICE ICE CUBES
- STIF: STRONG INOX FRAME. SOLID MACHINE STRUCTURE IN 4 COLUMNS WITH AISI 304 STAINLESS STEEL FRAME
- STRONGEST DOOR IN THE MARKET. MADE OF STAINLESS STEEL. OPENING AND DAMPING SYSTEM PATENTED BY ITV.
- FRONT VENTILATION CONCEPT: FRONTAL IN-OUT AIR SYSTEM ALLOWS ´BUILT IN´ MACHINES
- CLEANING SWITCH: ALLOWS CIRCULATION OF WATER WITH DESCALING PRODUCT (CALKLIN OR SIMILAR) WITHOUT COOLING.
- "NEVER STOP" MOTOR PUMP DEVELOPED BY ITV. PUMP WITHOUT SEALS, WHICH AVOIDS DETERIORATION IN HARD WATER
- EASI: EASY ACCESS FOR SERVICE & INSTALLATION. ALL PANELS CAN BE DISASSEMBLED SEPARATELY.
- ON/OFF LIGHTED ROCKER SWITCH IN FRONT PANEL
- TROPICALIZED MACHINES (T CLASS) / HEIGHT ADJUSTABLE LEGS FROM 37" TO 39"

EASI Easy Access for Service & Installation

STIF Strong Inox Frame

FRONT VENTILATION

	24 H lbs	70°F/21°C | 50°F/10°C lbs (Kg)	90°F/32°C | 70°F/21°C lbs (Kg)	STOCK lbs (Kg)	in (mm)	in (mm)
SPIKA NG 285 A		**323** (146)	**267** (121)	**99** (45)	Width **30"** (762) Depth **30"** (762) Height* **33"** (838)	Width **33"** (835) Depth **33"** (835) Height **38"** (970)
SPIKA NG 285 W		**323** (146)	**267** (121)			

SPIKA HALF DICE
0,9" (W) x 0,4" (D) x 1" (H)
23 mm (W) x 11 mm (D) x 26 mm (H)
Average dimensions

SPIKA FULL DICE
1" (W) x 0,9" (D) x 1" (H)
26 mm (W) x 23 mm (D) x 26 mm (H)
Average dimensions

* WITH LEGS 37"/39"

ACCESSORIES

INCLUDED

WATER OUTLET HOSE

4 HEIGHT ADJUSTABLE LEG KIT

SCOOP

NOT INCLUDED (OPTIONAL)

11" FILTER
ANTI-LIMESCALE + ANTI-CHLORINE
CS-111 K

11" REPLACEMENT CARTRIDGE
ANTI-LIMESCALE + ANTI-CHLORINE
CS11

SCALE KLEEN